

## 2. Tightening torques : Wheels

N.B. : A double tightening is a tightening to the torque followed by unscrewing then a tightening to the torque.

Vehicles		Steel rims	Aluminium rims
ION		10 daNm	10 daNm
106		9 daNm	10 daNm
107		10 daNm	10 daNm
1007		9 daNm	10 daNm
205		9 daNm	10 daNm
206		10 daNm	10 daNm
206+		9 daNm	10 daNm
207 i (Iran)		9 daNm	10 daNm
207		10 daNm	10 daNm
207 restyled		10 daNm	10 daNm
207 (Mercosur/China/Ascan)		10 daNm	10 daNm
208		10 daNm	10 daNm
301		10 daNm	10 daNm
306		9 daNm	10 daNm
307		9 daNm	10 daNm
308		10 daNm	10 daNm
308 (China/Russia)		10 daNm	10 daNm
RCZ		-	10 daNm
405		9 daNm	10 daNm
405 (Iran)		9 daNm	10 daNm
406		9 daNm	10 daNm
407		9 daNm	10 daNm
408 (China/Russia)		10 daNm	10 daNm

<http://127.0.0.1:6090/affiche.do?ref=B2GB0103P0&refaff=B2GB0103P0&typeDoc=2&id...> 1/11/2024